

Overview

Arburg 920 S 5000-2100, 2007


Arburg

Product number: 20053

Price

Price on request

Prices excl. VAT plus shipping costs



Description

* All prices excl. VAT plus shipping costs and possible delivery charges, if not stated otherwise.

terms of delivery: EXW (ex Works)
delivery time: on request
terms of payment: 100% prior to delivery

Product information

01-manufacturer:	Arburg
02-type:	A920 S 5000-2100
03-year of construction:	2007
04-condition:	überarbeitet
05-operating hours:	ca. 69.000
10-CLAMPING UNIT:	-
11-clamping force:	500 t
12-opening path:	900 mm
13-mould installation height min:	400 mm
14-mould installation height max.:	1050 mm
15-tie bar distance (h x v):	920 x 920 mm
16-plate dimension (h x v):	1340 x 1375 mm
17-centering (fix- movingplate):	200 / 200 mm
20-INJECTION UNIT:	IU2100
21-screw diameter:	70 mm
22-injection weight in polystyrol:	984 g
23-stroke volume:	1078 cm ³
24-injection pressure:	2.000 bar
30-CONTROL:	Selogica
31-screen language:	DE
32-operating manuel:	DE

40-EQUIPMENT:	Dichtsätze Schließ- und Spritzseitig neu / Sealing kits new on closing and injection side
41-core pulls:	2
42-air valves:	-
43-hot runner control devices :	15
44-robot interface:	Euromap 67
45-other equipment :	Handling auf Anfrage: W822-1707, 2016, x - Achse 550, Y - 1200, Z - 2500, C - Achse kpl., B- Achse 0°/270° pneum., 2 x Vakuum, 2 x Luft
50-GENERAL DATA:	-
51-installed heating capacity:	33,9 kW
52-pump drive power:	75,0 kW
53-total installed power:	108,9 kW
54-total weight:	25.000 kg
55-total size L x B x H:	9,1 x 2,2 x 2,50 m