

Overview

Demag EL-EXIS S 250/630-1450, 2007

Demag

Product number: 0-20028



Price

Price on request

Prices excl. VAT plus shipping costs

Description

terms of payment: 100% prior to delivery
delivery time: on request
terms of delivery: ex location

Product information

01-manufacturer:	Demag
02-type:	EL-EXIS S 250/630-1450
03-year of construction:	2007
04-condition:	Running Production
05-operating hours:	ca. 67.000
10-CLAMPING UNIT:	-
11-clamping force:	250 t
12-opening path:	670 mm
13-mould installation height min:	330 mm
14-mould installation height max.:	830 mm
15-tie bar distance (h x v):	630 x 630 mm
16-plate dimension (h x v):	950 x 950 mm
17-centering (fix- movingplate):	125/125 mm
20-INJECTION UNIT:	IU1450 (L/D25)
21-screw diameter:	50 mm (Mischteil)
22-injection weight in polystyrol:	480 g
23-stroke volume:	530 cm ³
24-injection pressure:	2.426 bar
30-CONTROL:	NC4
31-screen language:	DE
32-operating manual:	DE

40-EQUIPMENT:	-
41-core pulls:	4
42-air valves:	-
43-hot runner control devices :	40
44-robot interface:	Euromap 67
45-other equipment :	IU1450, L/D25 mit Mischteilschnecke
50-GENERAL DATA:	-
51-installed heating capacity:	14,8 kW
52-pump drive power:	106,0 kW
53-total installed power:	Motor + Heizung
54-total weight:	14.200 kg
55-total size L x B x H:	6,5 x 2,0 x 2,3 m