

Overview

Demag IntElect 210/580-1000, 2009

Demag


Product number: 50041



Price

Price on request

Prices excl. VAT plus shipping costs



Description

* All prices excl. VAT plus shipping costs and possible delivery charges, if not stated otherwise.

Frachtbasis: FCA Pegnitz

Lieferzeit: nach Absprache

Zahlungsbedingung: 100% vor Übernahme der Maschine, rein netto

Product information

01-manufacturer:	Demag
02-type:	IntElect 210/580-1000
03-year of construction:	2009
04-condition:	aus laufender Produktion / out of running production
05-operating hours:	ca. 28.000
10-CLAMPING UNIT:	-
11-clamping force:	210 t
12-opening path:	575 mm
13-mould installation height min:	340
14-mould installation height max.:	690 mm
15-tie bar distance (h x v):	580 x 580 mm
16-plate dimension (h x v):	855 x 860 mm
17-centering (fix- movingplate):	160/160 mm
20-INJECTION UNIT:	IU1000
21-screw diameter:	50 mm
22-injection weight in polystyrol:	393 g
23-stroke volume:	442 cm ³
24-injection pressure:	2.100 bar
30-CONTROL:	NC5
31-screen language:	DE
32-operating manuel:	DE

40-EQUIPMENT:	-
41-core pulls:	2 x (Hydr. Kernzug-Aggregat)
42-air valves:	1
43-hot runner control devices :	4
44-robot interface:	Euromap 67
45-other equipment :	Kernzug Beistellaggregat!
50-GENERAL DATA:	-
51-installed heating capacity:	14,8 kW
52-pump drive power:	entfällt
53-total installed power:	Motor + Heizung
54-total weight:	11.000 kg
55-total size L x B x H:	6,7 x 1,6 x 2,4 m