

Overview

Battenfeld TM Xpress 2700/1350, 2014

Product number: 20062

Battenfeld



Price

Price on request

Prices excl. VAT plus shipping costs



Description

terms of delivery: EXW (ex Works)
delivery time: on request
terms of payment: 100% prior to delivery

Product information

01-manufacturer:	Battenfeld
02-type:	TM Xpress 2700/1350
03-year of construction:	2014
05-operating hours:	ca. 35.000
10-CLAMPING UNIT:	-
11-clamping force:	270 t
12-opening path:	600 mm
13-mould installation height min.:	250 mm
14-mould installation height max.:	650 mm
15-tie bar distance (h x v):	630 x 630 mm
16-plate dimension (h x v):	940 x 1020 mm
17-centering (fix- movingplate):	-
20-INJECTION UNIT:	IU1350
21-screw diameter:	55 mm
22-injection weight in polystyrol:	588 g
23-stroke volume:	653 cm ³
24-injection pressure:	2.041 bar
30-CONTROL:	Unilog B6
31-screen language:	DE
32-operating manuel:	DE
40-EQUIPMENT:	-

42-air valves:	6
43-hot runner control devices :	-
44-robot interface:	Euromap 67
45-other equipment :	Robot auf Anfrage / Robot on request
50-GENERAL DATA:	-
51-installed heating capacity:	-
52-pump drive power:	55,0 kW
53-total installed power:	-
54-total weight:	12.500 kg
55-total size L x B x H:	7,20 x 2,1 x 2,34 m