

Overview

Arburg 630 A 2500-1300 Alldrive, 2017



Arburg

Product number: 50044

Price

Price on request

Prices excl. VAT plus shipping costs



Description

* All prices excl. VAT plus shipping costs and possible delivery charges, if not stated otherwise.

terms of delivery: FCA Pegnitz
delivery time: on request
terms of payment: 100% prior to delivery

Product information

01-manufacturer:	Arburg
02-type:	630 A 2500-1300 Alldrive
03-year of construction:	2017
05-operating hours:	ca. 22.900
10-CLAMPING UNIT:	-
11-clamping force:	250 t
12-opening path:	550 mm
13-mould installation height min:	300 mm
14-mould installation height max.:	750 mm
15-tie bar distance (h x v):	630 x 630 mm
16-plate dimension (h x v):	900 x 900 mm
17-centering (fix- movingplate):	125/125 mm
20-INJECTION UNIT:	IU1300
21-screw diameter:	55 mm
22-injection weight in polystyrol:	521 g
23-stroke volume:	570 cm ³
24-injection pressure:	2.470 bar
30-CONTROL:	Selogica direct
31-screen language:	DE
32-operating manuel:	DE
40-EQUIPMENT:	Selektierweiche 500x500, Förderband / Separator 500x500, conveyor belt

41-core pulls:	1
42-air valves:	3/2
43-hot runner control devices :	12
44-robot interface:	Euromap 67
45-other equipment :	Schnittstelle: Leitrechner OPC-UA + Temp.gerät (20mA) / Interface: master computer. OPC-UA, temperature control unit (20mA)
50-GENERAL DATA:	-
51-installed heating capacity:	30,9 kW
52-pump drive power:	entfällt
53-total installed power:	Motor + Heizung
54-total weight:	14.500 kg
55-total size L x B x H:	6,7 x 2,1 x 2,3 m