

## Overview

# Demag ergotech 110/470-600 System, 2005

Demag

Product number: 20070



## Price

**Price on request**

Prices excl. VAT plus shipping costs

## Description



terms of delivery: EXW (ex Works)  
delivery time: on request  
terms of payment: 100% prior to delivery

## Product information

<b>01-manufacturer:</b>	Demag
<b>02-type:</b>	ergotech 110/470-600 System
<b>03-year of construction:</b>	2005
<b>04-condition:</b>	Running Production
<b>05-operating hours:</b>	-
<b>10-CLAMPING UNIT:</b>	-
<b>11-clamping force:</b>	110 t
<b>12-opening path:</b>	600 mm
<b>13-mould installation height min:</b>	350 mm
<b>14-mould installation height max.:</b>	-
<b>15-tie bar distance (h x v):</b>	470 x 470 mm
<b>16-plate dimension (h x v):</b>	670 x 670 mm
<b>17-centering (fix- movingplate):</b>	125/125 mm
<b>20-INJECTION UNIT:</b>	IU600
<b>21-screw diameter:</b>	50 mm (Mischteil/mixing)
<b>22-injection weight in polystyrol:</b>	358 g
<b>23-stroke volume:</b>	398 cm <sup>3</sup>
<b>24-injection pressure:</b>	1.550 bar
<b>30-CONTROL:</b>	NC4
<b>31-screen language:</b>	DE
<b>32-operating manual:</b>	DE



<b>40-EQUIPMENT:</b>	-
<b>41-core pulls:</b>	2
<b>42-air valves:</b>	2
<b>43-hot runner control devices :</b>	16
<b>44-robot interface:</b>	Euromap 67
<b>50-GENERAL DATA:</b>	-
<b>51-installed heating capacity:</b>	15,7 kW
<b>52-pump drive power:</b>	30,0 kW
<b>53-total installed power:</b>	45,7 kW
<b>54-total weight:</b>	5700 kg
<b>55-total size L x B x H:</b>	4,9 x 1,6 x 2,0 m