

Product information

01-manufacturer:	Arburg
02-type:	Arburg 370S 700-170
03-year of construction:	2008
04-condition:	Running Production
05-operating hours:	ca. 73.000
10-CLAMPING UNIT:	-
11-clamping force:	70 t
12-opening path:	400 mm
13-mould installation height min:	200 mm
15-tie bar distance (h x v):	370 x 370 mm
16-plate dimension (h x v):	510 x 510 mm
17-centering (fix- movingplate):	125 / 125 mm
20-INJECTION UNIT:	IU170
21-screw diameter:	25/30/35 mm, wählbar!
22-injection weight in polystyrol:	45 g
23-stroke volume:	49 cm ³
24-injection pressure:	2.500 bar
30-CONTROL:	Selogica direct
31-screen language:	DE
32-operating manuel:	DE
40-EQUIPMENT:	Technologiestufe 2 / Technology Level 2

41-core pulls:	1
42-air valves:	ja / yes
43-hot runner control devices :	-
44-robot interface:	Euromap 67
45-other equipment :	Siehe Auftragspezifikation / see order specification
50-GENERAL DATA:	-
51-installed heating capacity:	11 kW
52-pump drive power:	15 kW
53-total installed power:	Motor + Heizung
54-total weight:	3.500 kg
55-total size L x B x H:	4,0 x 1,6 x 2,0 m