

## Overview

# ENGEL DUO 2460H/860W/1100WP COMBI, 2021


Engel

Product number: 40018

## Price

# Price on request

Prices excl. VAT plus shipping costs



## Description

terms of delivery: EXW (ex Works)  
delivery time: on request  
terms of payment: 100% prior to delivery

## Product information

<b>01-manufacturer:</b>	Engel
<b>02-type:</b>	DUO 2460H/860W/1100WP COMBI
<b>03-year of construction:</b>	2021
<b>04-condition:</b>	Running Production
<b>05-operating hours:</b>	ca. 14.650
<b>10-CLAMPING UNIT:</b>	-
<b>11-clamping force:</b>	1100 t
<b>12-opening path:</b>	2000 mm
<b>13-mould installation height min:</b>	700 mm
<b>14-mould installation height max.:</b>	1400 mm
<b>15-tie bar distance (h x v):</b>	1565 x 1310 mm
<b>16-plate dimension (h x v):</b>	2200 x 1990 mm
<b>17-centering (fix- movingplate):</b>	250 / 250 mm
<b>20-1. INJECTION UNIT:</b>	2460 H
<b>21-screw diameter:</b>	60 mm
<b>22-injection weight in polystyrol:</b>	817 g
<b>23-stroke volume:</b>	891 cm <sup>3</sup>
<b>24-injection pressure:</b>	2.250 bar
<b>30-2. INJECTION UNIT:</b>	860 W
<b>31-screw diameter:</b>	50 mm
<b>32-stroke volume:</b>	350 cm <sup>3</sup>

<b>33-injection weight in polystyrol:</b>	321 g
<b>34-injection pressure:</b>	1.455 bar
<b>40-CONTROL:</b>	CC300
<b>41-screen language:</b>	DE
<b>42-operating manuel:</b>	DE
<b>50-EQUIPMENT:</b>	Holmverlängerung 200 mm, 2-Stationen Drehtisch RD 1.800mm, Drehbewegung 180° pendelnd gegen Festanschlag. KUKA 6-Achsen Robot
<b>51-core pulls:</b>	4 + 1 (je bewegliche + feste Platte) / (per movable + fixed panel)
<b>52-air valves:</b>	ja
<b>53-hot runner control devices:</b>	48
<b>54-robot interface:</b>	easix KUKA150R, integriert
<b>55-other equipment:</b>	Siehe AB / OC
<b>60-GENERAL DATA:</b>	-
<b>61-installed heating capacity:</b>	20,5 + 12,2 kW
<b>62-pump drive power:</b>	140 kW
<b>63-total installed power:</b>	Motor + Heizung
<b>64-total weight:</b>	60.000 kg
<b>65-total size L x B x H:</b>	11,9 x 3,7 x 2,9 m