

Overview

Moretto volumetric dosing unit (fast) DVM8V

Moretto

Product number: DVM8V

Price

€2,271.54*

Prices excl. VAT plus shipping costs



Artikelnummer: DVM8V

ENGINEERING CLASSICS

MORE TO

VOLUMETRIC DOSING UNIT

DVM

Features

Model	Capacity (kg)	Max. gph	Max. height (mm)	Max. weight (kg)
DVM 1	1	10	100	10
DVM 2	2	20	200	20
DVM 3	3	30	300	30
DVM 4	4	40	400	40
DVM 5	5	50	500	50
DVM 6	6	60	600	60
DVM 7	7	70	700	70
DVM 8	8	80	800	80
DVM 9	9	90	900	90
DVM 10	10	100	1000	100

ENGINEERING CLASSICS

MORE TO

VOLUMETRIC DOSING UNIT

DVM

Dimension table

Model	Capacity (kg)	Max. throughput (kg/h)	Max. hopper height (mm)	Max. hopper width (mm)	Max. hopper length (mm)	Max. hopper depth (mm)	Max. hopper height (mm)	Max. hopper width (mm)	Max. hopper length (mm)	Max. hopper depth (mm)	Max. hopper height (mm)	Max. hopper width (mm)	Max. hopper length (mm)	Max. hopper depth (mm)
DVM 1	1	10	100	100	100	100	100	100	100	100	100	100	100	100
DVM 2	2	20	200	200	200	200	200	200	200	200	200	200	200	200
DVM 3	3	30	300	300	300	300	300	300	300	300	300	300	300	300
DVM 4	4	40	400	400	400	400	400	400	400	400	400	400	400	400
DVM 5	5	50	500	500	500	500	500	500	500	500	500	500	500	500
DVM 6	6	60	600	600	600	600	600	600	600	600	600	600	600	600
DVM 7	7	70	700	700	700	700	700	700	700	700	700	700	700	700
DVM 8	8	80	800	800	800	800	800	800	800	800	800	800	800	800
DVM 9	9	90	900	900	900	900	900	900	900	900	900	900	900	900
DVM 10	10	100	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000

* All prices excl. VAT plus shipping costs and possible delivery charges, if not stated otherwise.

Description

- new
- throughput 70 - 1400 gr. / hour
- direct adjustment of the percentage
- stainless steel dosing screw with patented profile
- memory for up to 100 recipes

The Moretto DVM series is the simplest solution for dosing masterbatch or additives. The direct setting of the percentage of the quantity to be dosed simplifies communication with the operator. The motorised dosing screw, controlled by an inverter, guarantees reliability. The dosing screw can be timed out. The inclined and guided dosing screw ensures maximum stability and precision. Stainless steel augers with a patented profile are available in various diameters for perfect dosing.

Product information

Gesamtgewicht:	20 kg
Gesamtgröße L x B x H:	36,8 x 37,3 x 38,7 cm
Schneckendurchmesser:	8 mm
Steigung der Schnecke:	4 mm
Trichterkapazität:	6 L
condition:	neu
elektrische Leistung:	0,09 kW
throughput min.-max.:	70 - 1400 gr. / Std.